



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## CHAMAK CEMENT PAINT

Chamak Cement Paint is very economical and ideal decorative Wall Finish for exterior and interior surfaces. It is based on the finest cement and high grade pigments.

Finish	: Smooth, water repellent finish.
Colour	: As per shade card.
Covering Capacity	: 4-6 Sq. meters per Kg per coat on a prepared surface.
Drying Time	: Sets after 6-8 hours prior to application of each coat and at the end of the day surface should be wetted with water. No Primer needed for sand faced plasters, cement sheets and concrete bricks.
Flash Point	: N.A
Thinner Recommended	: Add one litre of water per Kg of Cement Paint.
Method of Application	: By brush Two Coats are adequate.
Uses	: Ideal for interior and exterior surfaces like sand faced plasters, abestos cement sheets, concrete brick work etc. should not be used over enamels or black paints.
Application Areas	: exterior brick works & plastered surfaces.
Direction of Use	: Make creamy paste with 20% water slowly, then thin down further with 25% water, serve the mixed through ordinary cotton cloth before application.
Packing	: 5Kg, 25Kg