



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## CHAMAK ULTRA EXTERIOR EMULSION

A high-build formulation based on a tough, flexible resin, this water-based coating gives excellent long-term protection to exterior masonry, brickwork, rendering and concrete, besides a fine-textured finish of exceptional beauty, opacity and adhesion. In keeping with its name, it has anti-fungal, anti-flaking, anti-fading properties, and the unique 'one-way barrier' - a special osmotic property of the paint film that allows moisture to 'breathe out' and not let outside moisture in.

Finish	: Fine textured, matt
Colour	: As per shade card.
Drying Time	: 1-2 hrs. H.D - 4-6 hrs
Flash Point	: N.A.
Thinner Recommended	: Water
Application Areas	: By Trowel / roller / airless spray
Undercoats	: Textured thinned with water (1:1 by volume) as a primer coat to reduce surface porosity.
Shelf Life	: 12 Months
Uses	: Cement, sand surfaces, brickwork, rough cast concrete blocks, fibre boards and cement paint coated surfaces.
Covering Capacity	: 6.5 to 7.5 sq. metres per litre per coat depending on the surface and shade.
Application Areas	: Cementous, asbestos & brickwork , plastered surfaces.
Packing	: 1 ltr, 4 ltr, 10 ltr, 20 ltr.