



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



CHAMAK WALLCOAT POWDER PUTTY

Chamak Wall Putty is a white cement based putty. It provides a protective base for your expensive paints. Its superior water resisting properties prevent the paint from flaking even if the wall are damp.

- Finish** : Available in FINE & COARSE (MATT) finish.
- Drying Time** : Atleast 3 hours.
- Thinner Recommended** : Water is Used for Thining.
- Method of Application** : Exterior & Interior Walls of any building where an aesthetic/decorative coating is desired. Buildings like Houses, offices, Shopping-Malls, bungalows, Outhouses, Farmhouses, Stadiums, Trade & Technology Parks, Educational Institutes, Convention Centers, Airport & Railway Stations, Operas & Theaters, Museums & Exhibition Halls and even Flyover Walls.
- Shelf Life** : Should be stored in a dry place, Shelf life is six months.
- Uses** : Coarse Putty levels the wall surface. Fine Putty provides a thin skin-coat, which acts as a protective base for expensive paint.
- Covering Capacity** : The coverage area on normal smooth mortar wall is 20-25 sq ft/kg/mm in double coat. The coverage area will however will depend on the substrate.
- Direction of Use** : Use Chamak wall putty-fine on plastered surface, as a protective base-coat before you apply expensive paint. If the plaster is made with Grey Cement, use Chamak wall putty-coarse to level the surface. Generally, a 6-10 mm coat of this product will remove the undulations. Over Coarse Putty substrate, apply 1.0-1.5 mm coat of Chamak wall Putty-fine, to smoothen the surface and provide a protective undercoat for expensive paint. The White base will also ensure that the true tone of any shade/colour of paint will stand-out especially pastel shades.
- Packing** : 5kg & 20kg Packs