



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



CHAMAK REAL ACRYLIC EMULSION

Chamak Real Acrylic Emulsion is an exquisite emulsion paint that provides a luxurious finish and a silky glowing appearance to your walls.

Finish	: Luxurious silky glowing finish.
Colour	: Thousands of colour as per shade card
Drying Time	: Sarfac Dry Time : 15-25 Minutes. Complete Dry Time 3-4 hrs.
Flash Point	: Chamak Real is a water based paint which is not flammable.
Thinner Recommended	: Water
Method of Application	: By Brush, Roller, Spray. Apply 2 Coats of Chamak Real Acrylic Emulsion for repainting and 3 coats for fresh surface painting
Undercoats	: Chamak cement primer ST/WT
Shelf Life	: 3 Years from the date of manufacture in original tightly closed container. Stay away from direct sunlight and excessive heat. Stability of Thinned Paint : Use within 24 hrs.
Uses	: Chamak Real Acrylic Emulsion is an interior wall finish that can be applied on all types of smooth plasters, false ceilings, asbestos sheets, concrete etc.
Covering Capacity	: On smooth primary masonry surface by brushing:1 Coat: 26-30 sq mtr/ltr.2 Coats : 14-16 sq mtr/ltr.
Application Areas	: Interior walls, smooth plasters, False ceilings, asbestos sheets, concrete etc.
Packing	: 1ltr, 4ltr, 10ltr, 20ltr.