



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



CHAMAK SILK ACRYLIC EMULSION

Chamak Silk Acrylic Emulsion is specially formulated for those who want nothing but the best.

- Finish : Clean, Smooth (Egg shell) Slight Sheen, washable finish.
- Colour : It is supplied in cool elevating shades which give a fresh, clean look even after years of Painting.
- Drying Time : Surface Dry 1 hour Recoatable over night. Normally two coats are enough.
- Flash Point : Above 38⁰ C
- Thinner Recommended : Water
- Application Area : On brickworks or preparing base for sign boards.
- Undercoats : Self or previously prepared surface.
- Shelf Life : 12 Months
- Uses : It has all the qualities required for the interiors of a dreamhome. Ideal coating for interior decoration of houses, plastered walls, brick work, concrete and wood etc.
- Covering Capacity : 20-24 Sq. meters per. liter per coat
- Application Areas : By brush/Roller/Spray. Surfaces should be free efflorescence. Old distemper/Lime Should be removed by scraping or rubbing down and the surface should be free from Loose and flaking materials Suitable primer should be used applying.
- Packing : 1ltr, 4ltr, 10ltr, 20ltr.
- Highlights : Eco-Friendlyl paint with very good finish at economical prices