



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## CHASSIS ENAMEL

CHAMAK chassis Enamel is quick drying, economically priced, corrosion resistance glossy paint. It possesses excellent mechanical properties such as impact and abrasion resistance. Electrical insulating properties are also good & very water resistance.

Recommended use	:	Chamak Chassis Enamel is recommended for coating of motor vehicle chassis for protection from corrosion.
Finish	:	Smooth & glossy
Colour	:	Black, Red & Grey (Tata Steel Grey)
Covering Capacity on Smooth Mild steel Surface	:	N13 to 14 sq. mt./lit./coat by brushing for 20 micron dry film thickness.
Drying Time	:	Surface dry - Maximum 2 hours. Hard Dry - Less than 15 hours. (Above all properties depend upon temperature and humidity)
Flash Point	:	Above 30°C (86°F)
Thinner Recommended	:	CHAMAK syn. G.P. Thinner
Method of Application	:	By brush or spray at a pressure of 40 to 50 P.S.I.
Direction for use	:	Surface should be free from rust, grease, oil, moisture and loose flakes. Apply by brush or spray using recommended thinner if required. Allow to dry hard before applying second coat. Stir well prior to use.
Packing	:	20Liters, 4Liters, 1Liters & 500 mls.