



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



CHAMAK ACRYLIC WALL PUTTY

Chamak Acrylic Wall Putty is a readymade emulsion putty with excellent smoothness & superior whiteness which serves as a filler/leveller in a paint system. It also enhances durability of the paint system.

Finish	: Smooth Finish, superior whiteness
Colour	: White
Drying Time	: Touch dry-15 min max. Hard Dry 4 hrs max. (4-6 mil wet film thickness) Overcoating time - 10 to 12 hours Minimum.
Flash point	: N.A Water based
Thinner Recommended	: Water
Method of Application	: By trowel
Recommended Primer	: Chamak Cement Primer
Shelf Life	: 6 months
Uses	: Serves as a filler/leveller in a paint system
Covering Capacity	: Depends on texture of the substrate, in the range of 10-30 sqft per kg.
Application Areas	: On bricks works and plastered surfaces etc.
Packing	: 1kg, 5kg, 10kgs, 20kgs.