

## **Chamak Paintchem Limited**



1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350. (Gujarat) INDIA. ■ Ph.: 079-22703603, 22704607 ■ FAX: 079-22704815

Email: info@chamakpaint.com ■ URL: www.chamakpaint.com

## **CHAMAK INDTINT INDUSTRIAL COLORANTS**

Chamak industrial colorants designed for in-plant tinting. It is compactable with high performance solvent based industrial & maintenance coatings. It provides excellent dispersions and wetting properties, a wide range of hues, durability, Light fastness and chemical resistance.

Colour : 10 colours including Black.

Drying Time : No effect on drying of the base where desired shade is

to make

Flash Point : Above 58°c

Thinner Recommended : As suitable with the paint.

Uses : Recommended for tinting in paints like Epoxy Paints,

Polyurethane Paint, Chlorinated Rubber Paint.

Nitrocellulose Paint

Undercoats : Not required

Shelf Life : 2 Years.

Covering Capacity : It is for tinting purpose

Application Areas : All decorative and stoving paints.

Direction of Use : Add a little of the Universal Colorants at a time to the

paint to be tinted and stir well, Repeat till desired shade

is obtained.

Packing : 50ltr, 25ltr, 200ml, 100ml, 50ml Plastic bottles.