



# Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.  
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815  
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



## CLEAR GLOSSY, MATT & N. C. CLEAR

This is one fast drying Nitrocellulose (Clear) Lacquer formulated incorporating selected grades of Nitrocellulose, Special non-oxidising resins, plasticizers etc. It has very good water, petrol and lub. oil resistance.

- Recommended Use** : As a finishing clear varnish (Lacquer) on wood. As a finishing top coat for cars, two-wheelers, transport vehicles, light engineering ("white-goods") products etc. Can be used for mixing in N.C.Lacquer paints.
- Finish** : Smooth & glossy.
- Covering Capacity on Smooth** : 12 to 14 sq. mt. / lit. / Coat depending upon surface and spraying loss @ 20 micron DFT.
- Drying Time** : Surface Dry : 5 minutes Hard Dry : approx 5 hours.
- Flash Point** : Above 25° C
- Thinner Recommended** : CHAMAK N.C.Thinner 199  
CHAMAK N.C.Thinner 111
- Method of Application** : By spray @ 45 p.s.i.
- Directions For Use** : Remove dirt, oil-grease, dust etc. from the substrate. Clean the surface thoroughly. Adjust the viscosity of clear lacquer to about 18 sec. by FC-B4 using recommended thinner.
- Packing** : 20 Lit, 10 Lit, 4 Lit, 1 Lit, 500 ml
- Note** : During high humid climate, use up to 25% NC Retarder to minimise blushing.