



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



NC PRIMER SURFACER

Ideal for new wood, Chamak NC Primer surface has excellent filling properties and is specially formulated to prevent the 'sinkage' of gloss that occurs when synthetic enamels are applied directly on wood.

Finish	: Smooth and Matt
Colour	: White or Pigmented colours.
Drying Time	: Surface dry 2 hours. Hard dry : 4-6 hours.
Flash Point	: Above 38 ⁰ C
Thinner Recommended	: Chamak NC Thinner
Method of Application	: By Brush/Spray/Roller.
Undercoats	: Self
Self Life	: 12 months
Directions of Uses	: Chamak NC Primer should be brushed in properly to ensure that it is worked into the surface in order to prevent 'sinkage' of gloss on the top coats of enamels applied. The primed surface should be dry cut with emery paper no. 280 before finish coats are applied.
Covering Capacity	: 8 to 9 sq. metres per litre per coat, depending on the surface and the quality of wood.
Application Area	: On all wooden surfaces
Packing	: 500ml, 1Ltr, 4Ltr, 10Ltr, 20Ltr.
Highlights	: Support adhesion to finish coats and prevents penetration of wood.