



Chamak Paintchem Limited

1471, MAHAVIRNAGAR, P.O. THAKKARNAGAR, NATIONAL HIGHWAY, AHMEDABAD-382 350.
(Gujarat) INDIA. ■ Ph. : 079-22703603, 22704607 ■ FAX : 079-22704815
Email : info@chamakpaint.com ■ URL : www.chamakpaint.com



N.C. PUTTY (TROWLING COMPOUND)

CHAMAK N. C. Putty is airdrying Nitrocellulose, non oxidising Resin & Filler base putty, It has butter like consistency. It can be applied by putty knife. It is supplied ready to use consistency. It can be thinned to desired consistency by using recommended thinner, it dries hard. Its cutting is easy. It is used for filling dents and other surface imperfections.

Recommended	:	After application of recommended primer, it is used on metallic and wooden surfaces for filling surface imperfections and dents. It is recommended for cars, scooters, truck bodies, furnitures and table tennis top, etc.
Finish	:	Smooth & matt.
Colour	:	Grey
Drying Time	:	Surface Dry - 5 minutes. Hard Dry - 2 to 3 hours.
Flash Point	:	Above 25 ⁰ C (75 ⁰ F)
Consistency	:	Smooth and butter cut.
Thinner Recommended	:	CHAMAK N.C. Thinner No.111/199
Method of Application	:	By Putty Knife.
Recomended Primer	:	CHAMAK AUTO Primer of CHAMAK N.C.High Buil P.S.Grey.
Direction For use	:	Remove dirt, oil, grease, moisture and loose flakes, Surface shall be primed with recommended primer. Apply thin coats of CHAMAK N.C Putty with putty knife wherever is necessary with 15 to 20 minutes flash off between coats. Deep dents shall be filled in thin layers. After thorough drying, wet sand with suitable waterproof sand paper and apply CHAMAK P.S. Grey. use recommended thinner if required.
Shelf Life	:	As long as containers are kept sealed it can be stored up to 12 months without deterioration.
Packing	:	20 Litres, 4 Litres, 1 Litre, 500 mls.